

Fundamental Equations of Dynamics

KINEMATICS

Particle Rectilinear Motion

| Variable a | Constant $a = a_c$ |
|---------------------|-----------------------------------------|
| $a = \frac{dv}{dt}$ | $v = v_0 + a_c t$ |
| $v = \frac{ds}{dt}$ | $s = s_0 + v_0 t + \frac{1}{2} a_c t^2$ |
| $a ds = v dv$ | $v^2 = v_0^2 + 2a_c(s - s_0)$ |

Particle Curvilinear Motion

| x, y, z Coordinates | r, θ, z Coordinates |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| $v_x = \dot{x}$ $a_x = \ddot{x}$ | $v_r = \dot{r}$ $a_r = \ddot{r} - r\dot{\theta}^2$ |
| $v_y = \dot{y}$ $a_y = \ddot{y}$ | $v_\theta = r\dot{\theta}$ $a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$ |
| $v_z = \dot{z}$ $a_z = \ddot{z}$ | $v_z = \dot{z}$ $a_z = \ddot{z}$ |

n, t, b Coordinates

| | |
|---------------|-----------------------------------------------------------------------------|
| $v = \dot{s}$ | $a_t = \dot{v} = v \frac{dv}{ds}$ |
| | $a_n = \frac{v^2}{\rho}$ $\rho = \frac{[1 + (dy/dx)^2]^{3/2}}{ d^2y/dx^2 }$ |

Relative Motion

$$\mathbf{v}_B = \mathbf{v}_A + \mathbf{v}_{B/A} \quad \mathbf{a}_B = \mathbf{a}_A + \mathbf{a}_{B/A}$$

Rigid Body Motion About a Fixed Axis

| Variable α | Constant $\alpha = \alpha_c$ |
|-----------------------------------|-------------------------------------------------------------|
| $\alpha = \frac{d\omega}{dt}$ | $\omega = \omega_0 + \alpha_c t$ |
| $\omega = \frac{d\theta}{dt}$ | $\theta = \theta_0 + \omega_0 t + \frac{1}{2} \alpha_c t^2$ |
| $\omega d\omega = \alpha d\theta$ | $\omega^2 = \omega_0^2 + 2\alpha_c(\theta - \theta_0)$ |

For Point P

$$s = \theta r \quad v = \omega r \quad a_t = \alpha r \quad a_n = \omega^2 r$$

Relative General Plane Motion—Translating Axes

$$\mathbf{v}_B = \mathbf{v}_A + \mathbf{v}_{B/A(\text{pin})} \quad \mathbf{a}_B = \mathbf{a}_A + \mathbf{a}_{B/A(\text{pin})}$$

Relative General Plane Motion—Trans. and Rot. Axis

$$\mathbf{v}_B = \mathbf{v}_A + \boldsymbol{\Omega} \times \mathbf{r}_{B/A} + (\mathbf{v}_{B/A})_{xyz}$$

$$\mathbf{a}_B = \mathbf{a}_A + \dot{\boldsymbol{\Omega}} \times \mathbf{r}_{B/A} + \boldsymbol{\Omega} \times (\boldsymbol{\Omega} \times \mathbf{r}_{B/A}) + 2\boldsymbol{\Omega} \times (\mathbf{v}_{B/A})_{xyz} + (\mathbf{a}_{B/A})_{xyz}$$

KINETICS

~~Mass Moment of Inertia~~ $I = \int r^2 dm$

~~Parallel Axis Theorem~~ $I = I_G + md^2$

~~Radius of Gyration~~ $k = \sqrt{\frac{I}{m}}$

Equations of Motion

| | |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Particle | $\Sigma \mathbf{F} = m\mathbf{a}$ |
| Rigid Body (Plane Motion) | $\Sigma F_x = m(a_G)_x$ $\Sigma F_y = m(a_G)_y$ $\Sigma M_G = I_G \alpha$ or $\Sigma M_P = \Sigma (M_k)_P$ |

Principle of Work and Energy

$$T_1 + \Sigma U_{1-2} = T_2$$

Kinetic Energy

| | |
|----------|-----------------------|
| Particle | $T = \frac{1}{2}mv^2$ |
|----------|-----------------------|

| | |
|------------------------------|--------------------------------------------------|
| Rigid Body (Plane Motion) | $T = \frac{1}{2}mv_G^2 + \frac{1}{2}I_G\omega^2$ |
|------------------------------|--------------------------------------------------|

Work

Variable force $U_F = \int F \cos \theta ds$

Constant force $U_F = (F_c \cos \theta) \Delta s$

Weight $U_W = -W \Delta y$

Spring $U_s = -(\frac{1}{2}ks_2^2 - \frac{1}{2}ks_1^2)$

Couple moment $U_M = M \Delta \theta$

Power and Efficiency

$$P = \frac{dU}{dt} = \mathbf{F} \cdot \mathbf{v} \quad \epsilon = \frac{P_{\text{out}}}{P_{\text{in}}} = \frac{U_{\text{out}}}{U_{\text{in}}}$$

Conservation of Energy Theorem

$$T_1 + V_1 = T_2 + V_2$$

Potential Energy

$$V = V_g + V_e, \text{ where } V_g = \pm Wy, V_e = +\frac{1}{2}ks^2$$

Principle of Linear Impulse and Momentum

| | |
|----------|-------------------------------------------------------------|
| Particle | $m\mathbf{v}_1 + \Sigma \int \mathbf{F} dt = m\mathbf{v}_2$ |
|----------|-------------------------------------------------------------|

| | |
|------------|---------------------------------------------------------------------|
| Rigid Body | $m(\mathbf{v}_G)_1 + \Sigma \int \mathbf{F} dt = m(\mathbf{v}_G)_2$ |
|------------|---------------------------------------------------------------------|

Conservation of Linear Momentum

$$\Sigma(\text{sys. } m\mathbf{v})_1 = \Sigma(\text{sys. } m\mathbf{v})_2$$

Coefficient of Restitution $e = \frac{(v_B)_2 - (v_A)_2}{(v_A)_1 - (v_B)_1}$

Principle of Angular Impulse and Momentum

| | |
|----------|---------------------------------------------------------------------|
| Particle | $(\mathbf{H}_O)_1 + \Sigma \int \mathbf{M}_O dt = (\mathbf{H}_O)_2$ |
|----------|---------------------------------------------------------------------|

where $H_O = (d)(mv)$

| | |
|------------------------------|-------------------------------------------------------------------------------------------|
| Rigid Body (Plane motion) | $(\mathbf{H}_G)_1 + \Sigma \int \mathbf{M}_G dt = (\mathbf{H}_G)_2$ |
|------------------------------|-------------------------------------------------------------------------------------------|

where ~~$H_G = I_G \omega$~~

~~$(\mathbf{H}_O)_1 + \Sigma \int \mathbf{M}_O dt = (\mathbf{H}_O)_2$~~

where ~~$H_O = I_O \omega$~~

Conservation of Angular Momentum

$$\Sigma(\text{sys. } \mathbf{H})_1 = \Sigma(\text{sys. } \mathbf{H})_2$$